

PERFORMANCE 15W-40

AUTOMOTIVE

Lubricants



Description

Multigrade lubricant oil designed for use in light petrol vehicles. Recommended for petrol engines that require API SL quality level.

Properties

- Multigrade oil that keeps the engine clean.
- Its formulation minimises the formation of deposits and sludge.
- Protects the engine's metal parts against corrosion.
- Suitable for vehicles that use CNG or LPG as fuel.

Quality levels

- API SL

Technical characteristics

	UNIT	METHOD	VALUE
SAE grade			15W-40
Density at 15°C	g/ml	ASTM D4052	0.874
Viscosity at 100°C	cSt	ASTM D445	14
Viscosity at 40°C	cSt	ASTM D445	100
Viscosity at -20°C	cP	ASTM D5293	7000 max.
Viscosity index	-	ASTM D2270	143
Open cup flash point	°C	ASTM D92	215 min.
Pour Point	°C	ASTM D97	-39
TBN	mg KOH/g	ASTM D2896	6
Bosch injector shear: Viscosity at 100°C after shear	cSt	CEC-L-14-93	12.5 min.
NOACK volatility, 1h at 250°C	% weight	CEC-L-40-93	15 max.
HTHS viscosity at 150°C	cP	CEC-L-36-90	3.7 min.

The above mentioned characteristics are typical values and should not be considered product specifications.

A product safety sheet is available upon request.

repsol.com
+34 901 111 999

Lubricants technical data sheet. Revision 1. January 2018.