

# PERFORMANCE 10W-40

AUTOMOTIVE

Lubricants



## Description

Multigrade lubricant oil suitable for the engines of light petrol vehicles that only require API SL quality level. It provides great resistance to oxidation, increasing the time between oil changes. The oil's viscosity facilitates engine start-up.

## Properties

- Keeps the engine clean, reducing deposit formation and increasing service life.
- Contains anti-wear additives that minimise wear on the engine's parts.
- Suitable for vehicles that use CNG or LPG as fuel.

## Quality levels

- API SL

## Technical characteristics

	UNIT	METHOD	VALUE
SAE grade			10W-40
Density at 15°C	g/ml	ASTM D4052	0.871
Viscosity at 100°C	cSt	ASTM D445	13.5
Viscosity at 40°C	cSt	ASTM D445	91
Viscosity at -25°C	cP	ASTM D5293	7000 max.
Viscosity index	-	ASTM D2270	140 min.
Open cup flash point	°C	ASTM D92	215 min.
Pour Point	°C	ASTM D97	-40
TBN	mg KOH/g	ASTM D2896	6
Bosch injector shear: Viscosity at 100°C after shear	cSt	CEC L-14-93	11.5 min.
Noack volatility, 1 h at 250°C	% in weight	CEC L-40-93	15 max.
HTHS viscosity at 150°C	cP	CEC-L-36-90	3.5 min.

*The above mentioned characteristics are typical values and should not be considered product specifications.*

A product safety sheet is available upon request.

repsol.com  
+34 901 111 999

Lubricants technical data sheet. Revision 1. January 2018.